







| | PRODUCT CODE | DESCRIPTION | LENGTH (MM) | PACK SIZE | PRICE PER METRE | PRICE PER LENGTH | STOCK PACK | STOCK PACK PRICE PER METRE | STOCK PACK PRICE PER LENGTH |
|------------------------------------------------------------------------------------|--------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|-----------|-----------------|------------------|------------|----------------------------|-----------------------------|
| WALL TRACK | | | | | | | | | |
|  | | <i>A wall track to be fixed to wall for 2F3/2F4 furring channels to sit in around ceiling perimeters. Particularly useful for passageways.</i> | | | | | | | |
| | 2FW16 .30 | 16mm Furring Channel Perimeter Track | 3000 | 10 | 1.59 | 4.77 | 200 | 1.51 | 4.53 |
| | 2FW28 .30 | 28mm Furring Channel Perimeter Track | 3000 | 10 | 1.65 | 4.95 | 200 | 1.57 | 4.71 |
| EXPOSED CEILING SYSTEMS | | | | | | | | | |
|  | | <i>A "Balanced Tee" exposed ceiling grid for 1200mm x 600mm or 600mm x 600mm acoustic or plasterboard "Lay-In" ceiling tiles. Manufactured from galvanised steel with a white Colorbond capping, the main runners are self-splicing and the cross runners have "Click-In" tab-ends for fast installation. The joggled ends on the cross runners prevent "rolling" of the sections, ensuring a flat ceiling.</i> | | | | | | | |
| | 2T1 .36 | Donn Main Tee 24 x 38mm | 3600 | 20 | 1.83 | 6.59 | 20 | 1.83 | 6.59 |
| | 2T2 .12 | Donn Cross Tee 24 x 33mm | 1200 | 60 | 1.70 | 2.04 | 60 | 1.70 | 2.04 |
|  | 2T3 .06 | Donn Cross Tee 24 x 25mm | 600 | 60 | 2.27 | 1.36 | 60 | 2.27 | 1.36 |
|  | 2W2 .36 | Donn Wall Angle 22 x 19mm | 3600 | 40 | 1.74 | 6.26 | 40 | 1.74 | 6.26 |
|  | 2W1 .36 | Donn Wall Angle 40 x 19mm | 3600 | 32 | 2.11 | 7.60 | 32 | 2.11 | 7.60 |
|  | 2W3 .36 | Donn Shadowline Wall Angle 27 x 10 x 19mm For radius wall angles refer to PVC Mouldings & Trims Section. | 3600 | 24 | 2.03 | 7.31 | 24 | 2.03 | 7.31 |

**PRICING NOT CURRENT
NEW CATALOGUE UNDER CONSTRUCTION**



| PRODUCT CODE | DESCRIPTION | PACK SIZE | PRICE EACH | STOCK PACK | STOCK PACK PRICE EACH |
|------------------------------------------------------------------|-------------------------------------------------|-----------|------------|------------|-----------------------|
| DIRECT FIXING CLIPS - BATTEN | | | | | |
| <i>Direct Fix Clips to suit 2F1/2F6 Batten/Furring Channels.</i> | | | | | |
| 2D1 | Batten Clip-Short — 87mm | 100 | 0.29 | 1,000 | 0.28 |
| 2D2 | Batten Clip - Long — 160mm | 100 | 0.41 | 1,000 | 0.39 |
| 2D3 | Batten Wall/Ceiling Clip-Flush | 100 | 0.54 | 1,000 | 0.51 |
| 2D10 | Batten Wall/Ceiling Clip - 10mm Step | 100 | 0.54 | 1,000 | 0.51 |
| 2D11 | Batten Wall/Ceiling Clip-10mm Step 6mm Threaded | 100 | 0.79 | 1,000 | 0.75 |



| PRODUCT CODE | DESCRIPTION | PACK SIZE | PRICE EACH | STOCK PACK | STOCK PACK PRICE EACH |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------|-----------|------------|------------|-----------------------|
| DIRECT FIXING CLIPS - FURRING CHANNELS | | | | | |
| <i>Direct Fix Clips to suit 2F3/2F4 Furring Channels.</i> | | | | | |
| 2D5 | Furring Channel Clip - Short — 95mm | 100 | 0.31 | 1,000 | 0.29 |
| 2D6 | Furring Channel Clip - Long — 190mm | 100 | 0.77 | 1,000 | 0.73 |
| 2D7 | Furring Channel Wall/Ceiling Clip | 100 | 0.46 | 1,000 | 0.44 |
| 2D8 | Furring Channel Wall/Ceiling Clip 6mm Threaded | 100 | 0.65 | 1,000 | 0.61 |
| <i>An innovative adjustable furring channel clip for wall or ceiling. Any of the four positions can be used to support furring channel, therefore eliminating need of packing to ensure a flat surface when there are surface imperfections. These clips also allow for electrical cabling to run between furring channel and base structure.</i> | | | | | |
| 2D15 | Furring Channel Beta Fix Clip | 100 | 0.85 | 1,000 | 0.81 |
| <i>Furring Channels can also be direct fixed using resilient mounts. Refer to Page 11</i> | | | | | |



PRICING NOT CURRENT UNDER CONSTRUCTION
NEW CATALOG



| PRODUCT CODE | DESCRIPTION | PACK SIZE | PRICE EACH | STOCK PACK | STOCK PRICE EACH |
|-----------------------------------------------------------------|------------------------------------------------|-----------|------------|------------|------------------|
| ROD SUSPENSION COMPONENTS | | | | | |
| <i>Range of clips and fasteners to hang suspension rod from</i> | | | | | |
| 2H1 | Suspension Rod Bracket | 100 | 0.27 | 1,000 | 0.26 |
| 2H2 | Suspension Rod Bracket Right Angle | 100 | 0.27 | 1,000 | 0.26 |
| 2VF | Purlin Clip (VF1) | 100 | 0.31 | 1,000 | 0.29 |
| 2H7A | Tie Wire Spike 5mm hole 5 X 32 | 100 | | | prices page 73 |
| 2H7B | Tie Wire Spike 5mm hole 6.5 x 32 | 100 | | | prices page 73 |
| 2H10 | Pipe Spike with 6mm int. Thread | 100 | | | prices page 75 |
| 9S625 | Suspension Anchor Sleeve Type 6.5 x 25mm | 100 | | | prices page 72 |
| 9S640 | Suspension Anchor Sleeve Type 6.5 x 40mm | 100 | | | prices page 72 |
| 9S660 | Suspension Anchor Wedge Type 6.0 x 60mm | 100 | | | prices page 72 |
| 9WN06 | Wedge Nut for Bondek Roofing 6mm int. Thread | 100 | | | prices page 74 |
| 9AC25T | Angle Clip Assembly Powder Actuated | 100 | | | prices page 78 |
| 9TC632 | Threaded Clip Assembly - 6mm - Powder Actuated | 100 | | | prices page 78 |



| PRODUCT CODE | DESCRIPTION | PACK SIZE | PRICE EACH | STOCK PACK | STOCK PRICE EACH |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------|-----------|------------|------------|------------------|
| RESILIENT MOUNTS | | | | | |
| <i>A component to fix furring channel to walls or ceilings whilst isolating it from structure-vibration and reducing noise transmission from other areas. Resilient mounts with other methods of fixing are also available.</i> | | | | | |
| 2RD1 | Furring Channel Resilient Mount - Direct Fixing | 100 | 4.62 | 1,000 | 4.39 |
| 2RD1T | Furring Channel Resilient Mount - Threaded (No Fastener Supplied) | 100 | 5.73 | 500 | 5.45 |
| 2RD5 | Furring Channel to Top Cross Rail Resilient Mount | 100 | 5.62 | 500 | 5.34 |
| 2RD9 | Furring Channel Resilient Mount - Direct Fixing | 100 | 4.20 | 1000 | 3.99 |
| 2RD15 | Furring Channel "Beta Fix" Resilient Mount | 100 | 3.69 | 1000 | 3.49 |

NOT FOR CONSTRUCTION
 PRICING NOT FOR CONSTRUCTION
 NEW CATALOGUE UNDERWAY

| | PRODUCT CODE | DESCRIPTION | LENGTH (MM) | PACK SIZE | PRICE PER METRE | PRICE PER LENGTH | STOCK PACK | PRICE PER METRE | PRICE PER LENGTH |
|-----------------------------------------------------------------------------------|--------------|----------------------------------------------------------------------------------------------------------------------------------------|-------------|-----------|-----------------|------------------|------------|-----------------|------------------|
| SUSPENSION ROD/WIRE | | | | | | | | | |
|  | | <i>A plain galvanised rod/wire for use in suspending ceiling systems.</i> | | | | | | | |
| | 2R5 | Galvanised Rod - 5mm | 4000 | 40 | 0.55 | 2.20 | 1,000 | 0.52 | 2.08 |
| | 2R2 | Galvanised Wire - 2.5mm | 4000 | 160 | 0.25 | 1.00 | 640 | 0.24 | 0.96 |
|  | | <i>Metric 6mm All Thread and nuts for use in suspended ceiling applications. Other metric and imperial sizes available on request.</i> | | | | | | | |
| | 2RTA .30 | All Thread 6mm Metric (cut to size available) | 3000 | 100 | 1.92 | 5.76 | 500 | 1.82 | 5.46 |
| | *2RTA .015 | All Thread 6mm Metric | 150 | 100 | | 0.37 | 500 | | 0.35 |
| | 2RN | Nuts 6mm Metric | | 200 | | 0.06 | 200 | | 0.06 |
| | | <i>6mm Bolts available on request</i> | | | | | | | |
| UTILITY ANGLES | | | | | | | | | |
|  | *2UA 35.36 | 0.75 BMT Utility Angle 35 x 35mm x .8mm | 3600 | 20 | 1.72 | 6.19 | 100 | 1.64 | 5.90 |
| | *2UA 45.36 | 0.75 BMT Utility Angle 50 x 50mm x .8mm | 3600 | 20 | 2.44 | 8.78 | 100 | 2.32 | 8.35 |
| | | * Lead time may be required | | | | | | | |

PRICING NOT CURRENT
NEW CATALOGUE UNDER CONSTRUCTION

Ceiling Systems



| | PRODUCT CODE | DESCRIPTION | LENGTH (MM) | PACK SIZE | PRICE PER METRE | PRICE PER LENGTH | STOCK PACK | STOCK PACK PRICE PER METRE | STOCK PACK PRICE PER LENGTH |
|------------------------------------------------------------------------------------|--------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|-----------|-----------------|------------------|------------|----------------------------|-----------------------------|
| PRIMARY CHANNELS | | | | | | | | | |
|  | | <i>Used as a primary suspension channel to support furring channels. Can be suspended or direct fixed.</i> | | | | | | | |
| | 2P1 .36 | Top Cross Rail 25mm 0.55 BMT | 3600 | 10 | 1.46 | 5.26 | 200 | 1.38 | 4.97 |
| | 2P2 .36 | Top Cross Rail 25mm H/D 0.75 BMT Fire Tested | 3600 | 10 | 1.93 | 6.95 | 200 | 1.83 | 6.59 |
| | 2P2 .48 | Top Cross Rail 25mm H/D 0.75 BMT Fire Tested | 4800 | 10 | | 9.26 | 200 | | 8.78 |
| | *2P3 .48 | Radius Top Cross Rail 25mm | 4800 | 10 | 5.29 | 25.39 | 10 | 5.29 | 25.89 |
| | 2P4 .48 | Top Cross Rail 38mm | 4800 | 10 | 3.05 | 14.64 | 100 | 2.89 | 13.87 |
| BATTEN/FURRING CHANNELS | | | | | | | | | |
|  | | <i>A popular and versatile metal batten which can be directly nailed up, suspended or used on walls. Knurled face provides better contact for adhesive and positive screw point location.</i> | | | | | | | |
| | 2F1 .48 | Ceiling/Wall Batten 18mm 1200 Span | 4800 | 12 | 1.12 | 5.38 | 420 | 0.92 | 4.42 |
| | 2F1 .60 | Ceiling/Wall Batten 18mm 1200 Span | 6000 | 12 | | 6.72 | 420 | | 5.52 |
|  | 2F2 .61 | <i>Traditional domestic batten for direct fixing to trusses or walls</i> Top Hat Ceiling Batten | 6100 | 10 | 1.31 | 7.99 | 250 | 1.18 | 7.20 |
|  | | <i>Heavy duty furring channel 38mm wide, 28mm deep for building boards to be screw fixed to. Suitable for use in fire rated systems. Can be direct fixed with clips or fully suspended.</i> | | | | | | | |
| | 2F3 .36 | Furring Channel 28mm | 3600 | 4 | 1.61 | 5.80 | 240 | 1.58 | 5.51 |
| | 2F3 .48 | Furring Channel 28mm | 4800 | 4 | | 7.73 | 240 | | 7.34 |
| | 2F3 .60 | Furring Channel 28mm | 6000 | 4 | | 9.66 | 240 | | 9.18 |
|  | | <i>Medium duty furring channel, 38mm wide, 16mm deep for building boards to be screw fixed to. Can be direct fixed, fully suspended or used as wall batten.</i> | | | | | | | |
| | 2F4 .48 | Furring Channel 16mm | 4800 | 10 | 1.41 | 6.77 | 100 | 1.34 | 6.43 |
| | 2F4 .60 | Furring Channel 16mm | 6000 | 10 | | 8.46 | 100 | | 8.04 |
| | *2F5 .48 | Radius Furring Channel 16mm | 4800 | 1 | POA | POA | 1 | POA | POA |
|  | 2F7 .60 | <i>Recessed furring channel for direct fixing to walls, 13mm deep. Provides double screw fixing points for building boards.</i> | 6000 | 10 | 2.44 | 14.64 | 100 | 2.32 | 13.92 |
|  | 2F9 .36 | <i>A channel specifically designed for use on walls to provide sound isolation.</i> Resilient Channel | 3660 | 10 | 3.54 | 12.96 | 10 | 3.54 | 12.96 |
| | | *Lead time may be required | | | | | | | |

PRICING NOT CURRENT
NEW CATALOGUE UNDER CONSTRUCTION

Ceiling Systems